

# Metal Powerboard

**Product Code: PB4-6**

**PB4- 4 Outlet**

**PB6- 6 Outlet**

**PB8- 8 Outlet**

## **4 Way Metal Powerboard, Surge, EMI, RFI, Circuit Breaker**

Unique 4 way surge protected powerboard with METAL casing. Universal application and particularly beneficial in a workshop or commercial environment where normal powerboards may be easily damaged. Surge and overload protected with illuminated On/Off switch. EMI and RFI protection as well as handy wall mounting slots built into the casting. Spaced power socket to house bulky transformers and power packs. Bright orange colour for added safety.

Features:

- Voltage rating: 230~240Vac 50Hz.
- Current: 10A (Max).
- Power rating: 2400 Watt.
- 6 x 240 AC sockets.
- Protection Mode: Active – Neutral – Earth.
- Surge Current: 18,000A.
- Surge Protection: MOV (Metal Oxide Varistor).
- Typical Capacitance: 430pF.
- Clamping Voltage: < 275V (at 50A).
- Energy Absorption: 525 Joules.
- Response Time: < 20 nano seconds.
- Filtration protection: EMI and RFI.
- New “insulated pin” style SAA power plug.
- 1.2m length power cord.
- Supplied in heat sealed clamshell blister.



Specifications:

- Voltage Rating- 240VAC
- Current-10 Amps
- Power Rating- 2400 Watt
- APN- 9318054333885
- TUN Inner / Outer- 59318054333880 / 19318054333882

Warranty:

- 2 Year Limited Replacement

Shipping:

- Supplied in heat sealed clamshell blister.